



Specifications

■ Standard
 Optional
 N/A Not Applicable

Angle Boom - 48"

Angle Boom - 68"

Angle Boom - 84"

General

	Angle Boom - 48"	Angle Boom - 68"	Angle Boom - 84"
Operating Weight	118 kg	390 kg	428 kg
Length	1194 mm	1676 mm	1676 mm
Width	1397 mm	2007 mm	2413 mm
Height	584 mm	838 mm	838 mm
Bristle Material	Replaceable Polypropylene	Replaceable Polypropylene	Replaceable Polypropylene
Broom Angling	Manual	Hydraulic Cylinder	Hydraulic Cylinder
Broom Bristle Diameter	544 mm	813 mm	813 mm
Drive System	Hyd. Motor Chain Drive Reduction	Hyd. Motor, Direct Drive	Hyd. Motor, Direct Drive
Oscillation	Fixed	Fixed	Fixed
Sweep Width (Fully angled)	1054 mm	1600 mm	1956 mm
Sweep Width (Straight)	1219 mm	1727 mm	2134 mm
Flow Range Low	30,28 l/min	30,28 l/min	56,78 l/min
Flow Range High	49,21 l/min	90,85 l/min	105,99 l/min
Number of Bristle Sections - Zig Zag	23	36	44
Number of Bristle Sections - Straight	2	2	2
Sweep Width (Fully angled) @	30°	25°	25°
Number of Bristle Sections	27	n/a	n/a

Compatible Carriers

Skid-Steer Loaders			
Bobcat A770		■	■
Bobcat S70	■		
Bobcat S450		■	
Bobcat S510		■	■
Bobcat S530		■	■
Bobcat S550		■	■
Bobcat S570		■	■
Bobcat S590		■	■
Bobcat S595		■	■
Bobcat S630		■	■
Bobcat S650		■	■
Bobcat S740		■	■
Bobcat S750		■	■
Bobcat S770		■	■
Bobcat S850			■

Compact Track Loaders			
Bobcat T450		■	
Bobcat T550		■	■
Bobcat T590		■	■
Bobcat T595		■	■
Bobcat T630		■	■
Bobcat T650		■	■
Bobcat T740		■	■
Bobcat T750		■	■
Bobcat T770		■	■
Bobcat T870			■

Mini Track Loaders			
Bobcat MT52	■		
Bobcat MT55	■		
Bobcat MT85	■		

Toolcat™ Work Machine			
Bobcat 5600		■	■
Bobcat 5610		■	■

Telehandler			
Bobcat V417			■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.