



■ Standard   
  Optional   
 N/A Not Applicable

**Planer, Standard Flow - 14"**

**Planer, High Flow - 18"**

**Planer, High Flow - 24"**

**Planer, High Flow - 40"**

⊖ **General**

	Planer, Standard Flow - 14"	Planer, High Flow - 18"	Planer, High Flow - 24"	Planer, High Flow - 40"
<b>Operating Weight</b>	502 kg	539 kg	572 kg	1043 kg
<b>Length</b>	1206 mm	1206 mm	1206 mm	1118 mm
<b>Width</b>	1676 mm	1687 mm	1687 mm	1727 mm
<b>Height</b>	744 mm	894 mm	894 mm	813 mm
<b>Cutting Depth Max</b>	152 mm	152 mm	152 mm	127 mm
<b>Cutting Depth Min</b>	0 mm	0 mm	0 mm	0 mm
<b>Drum Width Max</b>	356 mm	457 mm	610 mm	1016 mm
<b>Number of Bits</b>	n/a	n/a	n/a	75
<b>Sideshift</b>	757 mm	757 mm	757 mm	650 mm
<b>Maximum Cutting Angle</b>	15°	15°	15°	8°
<b>Planing Distance Next to Curb</b>	1915 mm	1915 mm	2042 mm	76 mm
<b>Drum Diameter</b>	451 mm	451 mm	451 mm	368 mm

⊖ **Compatible Carriers**

<b>Skid-Steer Loaders</b>				
Bobcat A770	■	■	■	■
Bobcat S450	■			
Bobcat S510	■			
Bobcat S530	■			
Bobcat S550	■	■	■	
Bobcat S570	■	■	■	
Bobcat S590	■	■	■	
Bobcat S595	■	■	■	
Bobcat S630	■	■	■	
Bobcat S650	■	■	■	
Bobcat S740	■	■	■	
Bobcat S750	■	■	■	■
Bobcat S770	■	■	■	■
Bobcat S850		■	■	■

<b>Compact Track Loaders</b>				
Bobcat T450	■			
Bobcat T550	■	■	■	
Bobcat T590	■	■	■	
Bobcat T595	■	■	■	
Bobcat T630	■	■	■	
Bobcat T650	■	■	■	
Bobcat T740	■	■	■	
Bobcat T750	■	■	■	■
Bobcat T770	■	■	■	■
Bobcat T870		■	■	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.