

Attachments / Snowblower Specifications



■ Standard
 Optional
 N/A Not Applicable

Snowblower, SB150 - 36"
 Snowblower, SB150 - 48"
 Snowblower, SB200 - 60"
 Snowblower, SB200 - 66"
 Snowblower, SB200 - 78"
 Snowblower, SB240 - 72"
 Snowblower, SB240 - 84"
 Snowblower, SBX240 - 72"
 Snowblower, SBX240 - 84"

General

	Snowblower, SB150 - 36"	Snowblower, SB150 - 48"	Snowblower, SB200 - 60"	Snowblower, SB200 - 66"	Snowblower, SB200 - 78"	Snowblower, SB240 - 72"	Snowblower, SB240 - 84"	Snowblower, SBX240 - 72"	Snowblower, SBX240 - 84"
Operating Weight	194 kg	211 kg	356 kg	367 kg	390 kg	458 kg	485 kg	458 kg	501 kg
Length	940 mm	940 mm	978 mm	978 mm	978 mm	1100 mm	1100 mm	1128 mm	1128 mm
Width	1001 mm	1306 mm	1588 mm	1740 mm	2045 mm	1892 mm	2197 mm	1892 mm	2197 mm
Height	1280 mm	1280 mm	1549 mm	1549 mm	1549 mm	1664 mm	1664 mm	1661 mm	1661 mm
Steel Cutting Edge	.375x3.0 in. (9x76mm)	.375x3.0 in. (9x76mm)	.5x4.0 in. (13x102mm)	.5x4.0 in. (13x102mm)	.5x4.0 in. (13x102mm)	.5x4.0 in. (13x102mm)	.5x4.0 in. (13x102mm)	.5x4.0 in. (13x102mm)	.5x4.0 in. (13x102mm)
Intake Height	584 mm	584 mm	635 mm	635 mm	635 mm	859 mm	859 mm	876 mm	859 mm
Fan Diameter	381 mm	381 mm	508 mm	508 mm	508 mm	610 mm	610 mm	610 mm	610 mm
Auger Diameter	356 mm	356 mm	356 mm	356 mm	356 mm	457 mm	457 mm	470 mm	470 mm
Discharge Chute	Hydraulically Controlled	Hydraulically Controlled	Hydraulically Controlled	Hydraulically Controlled	Hydraulically Controlled	Hydraulically Controlled	Hydraulically Controlled	Hydraulically Controlled	Hydraulically Controlled
Discharge Chute Angle	276°	276°	270°	270°	270°	270°	270°	270°	270°
Throw Distance	Up to 25 feet (7.6 m)	Up to 25 feet (7.6 m)	Up to 40 feet (12.2 M)	Up to 40 feet (12.2 M)	Up to 40 feet (12.2 M)	Up to 40 feet (12.2 M)	Up to 45 feet (13.7 M)	Up to 45 feet (13.7 M)	Up to 45 feet (13.7 M)
Flow Required Min	32,2 l/min	32,2 l/min	54,9 l/min	54,9 l/min	54,9 l/min	94,6 l/min	94,6 l/min	132,5 l/min	132,5 l/min
Flow Required Max	56,8 l/min	56,8 l/min	121,1 l/min	121,1 l/min	121,1 l/min	121,1 l/min	121,1 l/min	159 l/min	159 l/min

Compatible Carriers

Skid-Steer Loaders									
Bobcat A770					■	■	■	■	■
Bobcat S70	■	■							
Bobcat S450			■	■					
Bobcat S510			■	■	■				
Bobcat S530			■	■	■				
Bobcat S550			■	■	■	■			
Bobcat S570			■	■	■	■			
Bobcat S590			■	■	■	■			
Bobcat S595			■	■	■	■			
Bobcat S630				■	■	■	■		
Bobcat S650				■	■	■	■		
Bobcat S740				■	■	■	■		
Bobcat S750				■	■	■	■	■	■
Bobcat S770				■	■	■	■	■	■
Bobcat S850					■		■		■

Compact Track Loaders									
Bobcat T450			■	■					
Bobcat T550				■	■	■			
Bobcat T590				■	■	■			
Bobcat T595				■	■	■			
Bobcat T630					■	■	■		
Bobcat T650					■	■	■		
Bobcat T740					■	■	■		
Bobcat T750					■	■	■	■	■
Bobcat T770					■	■	■	■	■
Bobcat T870							■		■

Mini Track Loaders									
Bobcat MT52	■	■							
Bobcat MT55	■	■							
Bobcat MT85	■	■							

Toolcat™ Work Machine									
Bobcat 5600			■	■		■			
Bobcat 5610			■	■		■			

Telehandler									
Bobcat V417					■				

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.