



Standard
 Optional
 N/A Not Applicable

Sand and Salt Spreader

HS8 Spreader

⊖ **General**

Operating Weight	147 kg	198 kg
Length	1994 mm	815 mm
Width	1232 mm	1382 mm
Height	1135 mm	1039 mm
Hopper Capacity	0,38 m ³	0,23 m ³
Spreading Pattern Min	1524 mm	737 mm
Spreading Pattern Max	12192 mm	8534 mm
Speed Control	Variable Speed Control Dial	Variable, Hydraulic
Motor	12-Volt DC Direct Drive	Hydraulic
Spinner Wheel	12" Diameter	18" diameter

⊖ **Compatible Carriers**

Skid-Steer Loaders		
Bobcat A770		■
Bobcat S450		■
Bobcat S510		■
Bobcat S530		■
Bobcat S550		■
Bobcat S570		■
Bobcat S590		■
Bobcat S595		■
Bobcat S630		■
Bobcat S650		■
Bobcat S740		■
Bobcat S750		■
Bobcat S770		■
Bobcat S850		■

Compact Track Loaders		
Bobcat T450		■
Bobcat T550		■
Bobcat T590		■
Bobcat T595		■
Bobcat T630		■
Bobcat T650		■
Bobcat T740		■
Bobcat T750		■
Bobcat T770		■
Bobcat T870		■

Toolcat™ Work Machine		
Bobcat 5600	■	■
Bobcat 5610		■

Telehandler		
Bobcat V417		■

Telehandler

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.