

Excavators / 418 Compact Excavator

Specifications & Options

Standard Optional N/A Not Applicable

Bobcat 418

⊖ Engine

Emissions Tier (EPA)	Tier 4
Engine Fuel	Diesel
Maximum Governed RPM	2,370 rpm
Horsepower	7.6 kW
Turbocharged Engine	N/A

⊖ Performance

Operating Weight	1176 kg
Weight Class	1 t
Travel Speed - High	2.8 km/h
Travel Speed - Low	2.1 km/h
Arm Digging Force	5,550 N
Bucket Digging Force	8,294 N
Boom Swing - Left	67°
Boom Swing - Right	64°
Maximum Dig Depth	1.8 m
Max Dump Height	1.8 m
Maximum Reach at Ground Level	3.1 m

⊖ Capacities

Fuel Tank	16 L
------------------	------

⊖ Hydraulic System

Auxiliary Std Flow	20 l/min
Auxiliary Pressure	190 bar

⊖ Dimansion

Length	2793 mm
Overall Length in Travel Position	2793 mm
Width	710 mm
Height	2209 mm

⊖ Features

Air Conditioning	N/A
Cab Enclosure	N/A
Cab Heater	N/A
Heater Air Conditioning	N/A
Radio	N/A
Tail Swing Type	Zero
Engine Shutdown	N/A
Auxiliary Hydraulics	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	N/A
Quick Tach System	N/A
Rubber Track	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	N/A
Angle Blade	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.