

# Excavators / E08 Compact Excavator

## Specifications & Options

■ Standard
  Optional
N/A Not Applicable

**Bobcat E08**

### ⊖ Engine

Standard

<b>Emissions Tier (EPA)</b>	Tier 2
<b>Engine Fuel</b>	Diesel
<b>Maximum Governed RPM</b>	2,000 rpm
<b>Horsepower</b>	7.6 kW
<b>Turbocharged Engine</b>	N/A

### ⊖ Performance

<b>Operating Weight</b>	1,138 kg
<b>Weight Class</b>	1 t
<b>Travel Speed - High</b>	2.1 km/h
<b>Travel Speed - Low</b>	N/A
<b>Arm Digging Force</b>	5,550 N
<b>Bucket Digging Force</b>	8,294 N
<b>Boom Swing - Left</b>	67°
<b>Boom Swing - Right</b>	64°
<b>Maximum Dig Depth</b>	1.8 m
<b>Max Dump Height</b>	1.8 m
<b>Maximum Reach at Ground Level</b>	3.1 m

### ⊖ Capacities

<b>Fuel Tank</b>	16 L
------------------	------

### ⊖ Hydraulic System

<b>Auxiliary Std Flow</b>	64 l/min
<b>Auxiliary Pressure</b>	185 bar

### ⊖ Dimansion

<b>Length</b>	2793 mm
<b>Overall Length in Travel Position</b>	2793 mm
<b>Width</b>	1000 mm
<b>Height</b>	2204 mm

### ⊖ Features

<b>Air Conditioning</b>	N/A
<b>Cab Enclosure</b>	N/A
<b>Cab Heater</b>	N/A
<b>Heater Air Conditioning</b>	N/A
<b>Radio</b>	N/A
<b>Tail Swing Type</b>	Minimal
<b>Engine Shutdown</b>	N/A
<b>Auxiliary Hydraulics</b>	■
<b>Secondary Auxiliary Hydraulics</b>	N/A
<b>Quick Tach System</b>	N/A
<b>Rubber Track</b>	■
<b>Selectable Auxiliary Hydraulic Flow</b>	N/A
<b>Angle Blade</b>	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.