

Excavators / E19 Compact Excavator

Specifications & Options

Standard
 Optional
 N/A Not Applicable

Bobcat E19

⊖ Engine

	Standard arm	Long arm
Emissions Tier (EPA)		Tier 4
Engine Fuel		Diesel
Maximum Governed RPM		2,500 rpm
Horsepower		10.4 kW
Turbocharged Engine		N/A

⊖ Performance

	Standard arm	Long arm
Operating Weight	1781 kg	1787 kg
Weight Class		2 t
Travel Speed - High		4 km/h
Travel Speed - Low		2.5 km/h
Arm Digging Force	10,371 N	9,279 N
Bucket Digging Force		20,835 N
Boom Swing - Left		80°
Boom Swing - Right		60°
Maximum Dig Depth	2.4 m	2.6 m
Max Dump Height	2.6 m	2.7 m
Maximum Reach at Ground Level	4.0 m	4.2 m

⊖ Capacities

Fuel Tank	19 L
-----------	------

⊖ Hydraulic System

Auxiliary Std Flow	30 l/min
Auxiliary Pressure	180 bar

⊖ Dimansion

Length	3831 mm	3812 mm
Overall Length in Travel Position	3831 mm	3812 mm
Width	980 mm	980 mm
Height	2299 mm	2299 mm

⊖ Features

Cab Enclosure	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Cab Air Conditioning	N/A
Radio	<input checked="" type="checkbox"/>
Tail Swing Type	Conventional
Engine Shutdown	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	N/A
Quick Tach System	N/A
Rubber Track	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input type="checkbox"/>
Angle Blade	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.