


Excavators / E26 Compact Excavator

Specifications & Options

 Standard Optional N/A Not Applicable

Bobcat E26

⊖ Engine

	Standard	Long Arm
Emissions Tier (EPA)	Tier 4	Tier 4
Engine Fuel	Diesel	
Maximum Governed RPM	2,500 rpm	2,500 rpm
Horsepower	18.5 kW	18.5 kW
Turbocharged Engine	N/A	N/A

⊖ Performance

Operating Weight	2570 kg	2763 kg
Weight Class	2.6 t	2.8 t
Travel Speed - High	4.5 km/h	4.5 km/h
Travel Speed - Low	2.4 km/h	2.4 km/h
Arm Digging Force	15,800 N	13,200 N
Bucket Digging Force	22,200 N	22,200 N
Boom Swing - Left	60°	
Boom Swing - Right	60°	
Maximum Dig Depth	2.6 m	2.9 m
Max Dump Height	3 m	3.2 m
Maximum Reach at Ground Level	4.6 m	4.9 m

⊖ Capacities

Fuel Tank	34,6 L
------------------	--------

⊖ Hydraulic System

Auxiliary Std Flow	47,3 l/min	
Auxiliary Pressure	180 bar	180 bar

⊖ Dimansion

Length	4327 mm	4327 mm
Overall Length in Travel Position	4327 mm	4327 mm
Width	1500 mm	1500 mm
Height	2412 mm	2412 mm

⊖ Features

Cab Enclosure	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cab Air Conditioning	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Radio	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Tail Swing Type	Minimal	Minimal
Engine Shutdown	<input type="checkbox"/>	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	N/A	N/A
Quick Tach System	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Rubber Track	<input type="checkbox"/>	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Angle Blade	N/A	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.