

Excavators / E32 Compact Excavator

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat E32

⊖ Engine

	Standard	Long Arm
Emissions Tier (EPA)	Interim Tier 4	Interim Tier 4
Engine Fuel	Diesel	
Maximum Governed RPM	2,400 rpm	2,400 rpm
Horsepower	24.8 kW	24.8 kW
Turbocharged Engine	N/A	N/A

⊖ Performance

Operating Weight	3294 kg	3600 kg
Weight Class	3.3 t	3.6 t
Travel Speed - High	4.7 km/h	4.7 km/h
Travel Speed - Low	2.6 km/h	2.6 km/h
Arm Digging Force	20,413 N	17,734 N
Bucket Digging Force	30,995 N	30,995 N
Boom Swing - Left	75°	
Boom Swing - Right	55°	
Maximum Dig Depth	3.1 m	3.4 m
Max Dump Height	3.3 m	3.5 m
Maximum Reach at Ground Level	5 m	5.3 m

⊖ Capacities

Fuel Tank	53.1 L
------------------	--------

⊖ Hydraulic System

Auxiliary Std Flow	64 l/min	
Auxiliary Pressure	206 bar	206 bar

⊖ Dimension

Length	4662 mm	4761 mm
Overall Length in Travel Position	4662 mm	4761 mm
Width	1520 mm	1520 mm
Height	2429 mm	2429 mm

⊖ Features

Cab Enclosure	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cab Air Conditioning	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Radio	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Tail Swing Type	Conventional	Conventional
Engine Shutdown	<input type="checkbox"/>	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Quick Tach System	<input type="checkbox"/>	<input type="checkbox"/>
Rubber Track	<input type="checkbox"/>	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input type="checkbox"/>	<input type="checkbox"/>
Angle Blade	N/A	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.