

Excavators / E62 Compact Excavator

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat E62

⊖ Engine

	Standard	Long Arm
Emissions Tier (EPA)		Tier 3
Engine Fuel		Diesel
Maximum Governed RPM		2,200 rpm
Horsepower		36.2 kW
Turbocharged Engine		N/A

⊖ Performance

	Standard	Long Arm
Operating Weight	6130 kg	6250 kg
Weight Class		6.3 t
Travel Speed - High	4.7 km/h	4.7 km/h
Travel Speed - Low	2.6 km/h	2.6 km/h
Arm Digging Force	29,300 N	26,200 N
Bucket Digging Force	44,100 N	44,100 N
Boom Swing - Left		70°
Boom Swing - Right		50°
Maximum Dig Depth	3.8 m	4.1 m
Max Dump Height	4 m	4.3 m
Maximum Reach at Ground Level	6.1 m	6.4 m

⊖ Capacities

Fuel Tank	78 L
------------------	------

⊖ Hydraulic System

Auxiliary Std Flow	85 l/min
Auxiliary Pressure	210 bar

⊖ Dimansion

	Standard	Long Arm
Length	5670 mm	5670 mm
Overall Length in Travel Position	5670 mm	5670 mm
Width	1980 mm	1980 mm
Height	2550 mm	2550 mm

⊖ Features

Cab Enclosure	■
Cab Heater	N/A
Cab Air Conditioning	■
Radio	■
Tail Swing Type	Minimal
Engine Shutdown	N/A
Auxiliary Hydraulics	■
Secondary Auxiliary Hydraulics	<input checked="" type="checkbox"/>
Quick Tach System	<input checked="" type="checkbox"/>
Rubber Track	■
Selectable Auxiliary Hydraulic Flow	N/A
Angle Blade	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.