

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat T110

⊖ Engine

Emissions Tier (EPA)	iT4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	28.9 kW
Turbocharged Engine	<input checked="" type="checkbox"/>

⊖ Performance

Rated Operating Capacity (SAE)	499 kg
Operating Capacity (50% of Tip)	721.5 kg
Tipping Load	1443 kg
Operating Weight	2379 kg
Travel Speed	8.4 km/h
Travel Speed (2-speed option)	13.5 km/h
Ground Pressure (Rubber)	0.32 bar

⊖ Capacities

Fuel Tank	45.2 l
------------------	--------

⊖ Hydraulic System

System Relief @ Quick Couplers	207 bar
Auxiliary Std Flow	47.5 l/min
Auxiliary High Flow	n/a

⊖ Dimansion

Length	2972.5 mm
Length without Attachment	2262.5 mm
Length with Standard Bucket	2972.5 mm
Width	1199.1 mm
Width (with bucket)	1270 mm
Height	1881.6 mm
Height with Operator Cab	1881.6 mm
Height to Bucket Hinge Pin	2634 mm
Reach @ Maximum Height	578.5 mm
Turning Radius	1852.2 mm
Length of track on ground	1298.7 mm
Track Width	250 mm

⊖ Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	■
Suspension Seat	■
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	■
Bob-Tach Attachment System	■
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.