Compact Track Loaders / T750 Compact Track Loader Specifications & Options

Standard Optional N/A Not Applicable	Bobcat T750
─ Engine	
Emissions Tier (EPA)	Tier 3
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	62,5 kW
Turbocharged Engine	✓

Performance

Rated Operating Capacity (SAE)	1611 kg
Operating Capacity (50% of Tip)	2073 kg
Tipping Load	4147 kg
Operating Weight	4663 kg
Travel Speed	10.6 km/h
Travel Speed (2-speed option)	17.2 km/h
Ground Pressure (Rubber)	0.28 bar

igoplus Capacities

Fuel Tank	166.4
-----------	-------

igoplus Hydraulic System

System Relief @ Quick Couplers	241,5 bar
Auxiliary Std Flow	87,1 l/min
Auxiliary High Flow	138,2 l/min

igoplus Dimansion

Length	3597 mm
Length without Attachment	2903 mm
Length with Standard Bucket	3597 mm
Width	1981 mm
Width (with bucket)	2032 mm
Height	2065 mm
Height with Operator Cab	2065 mm
Height to Bucket Hinge Pin	3353 mm
Reach @ Maximum Height	853 mm
Turning Radius	2235 mm
Length of track on ground	2075 mm
Track Width	450 mm

⊝ Features

Joystick Control	\checkmark
Air Conditioning	
Backup Alarm	
BICS System (Interlock)	
Cab Heater	\checkmark
Operating Lights	
Suspension Seat	
Two Speed Travel	ightharpoonup
Deluxe Instrumentation	\checkmark
Engine Shutdown	
Hydraulic Bucket Positioning	ightharpoonup
High Flow Option	✓
Auxiliary Hydraulics	
Bob-Tach Attachment System	
Power Bob-Tach	\checkmark
ACS (Switchable Controls)	✓
Ride Control	\checkmark
Horn	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.