

Mini Track Loaders / MT55 Mini Track Loader

Specifications & Options

Standard Optional N/A Not Applicable

Bobcat MT55

⊖ Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	900 cm ³
Number of Cylinders	3

⊖ Performance

Rated Operating Capacity (SAE)	249 kg
Tipping Load	730 kg
Operating Weight	1184 kg
Ground Pressure (Rubber)	0,34 bar
Travel Speed	5,6 km/h
Travel Speed - Reverse	2,3 km/h

⊖ Capacities

Fuel Tank	26,5 l
------------------	--------

⊖ Hydraulic System

Pump Capacity	45,4 l/min
System Relief @ Quick Couplers	199,95 bar
Auxiliary High Flow	n/a

⊖ Dimansion

Length	2365 mm
Width	904 mm
Height	1247 mm
Height to Bucket Hinge Pin	1808 mm
Length of track on ground	864 mm
Reach @ Maximum Height	462 mm

⊖ Features

Lift-Arm Support	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Spark Arrestor Muffler	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Reverse Travel Stop Panel	<input type="checkbox"/>
Wide Track	<input checked="" type="checkbox"/>
Neutral Start Interlocks	<input type="checkbox"/>
Lift Arm Lockout With Manual Bypass	<input type="checkbox"/>
Tilt Lockout	<input type="checkbox"/>
Built-In Tie Down & Crane/Lift Locations	<input type="checkbox"/>
Ride-on Platform	<input checked="" type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.