

Mini Track Loaders / MT85 Mini Track Loader

Specifications & Options

Standard Optional N/A Not Applicable

Bobcat MT85

⊖ Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	900 cm ³
Number of Cylinders	3

⊖ Performance

Rated Operating Capacity (SAE)	386 kg
Tipping Load	1115 kg
Operating Weight	1411 kg
Ground Pressure (Rubber)	0,34 bar
Travel Speed	6,4 km/h
Travel Speed - Reverse	3,9 km/h

⊖ Capacities

Fuel Tank	26,5 l
------------------	--------

⊖ Hydraulic System

Pump Capacity	45,4 l/min
System Relief @ Quick Couplers	199,95 bar
Auxiliary High Flow	n/a

⊖ Dimansion

Length	2697 mm
Width	904 mm
Height	1387 mm
Height to Bucket Hinge Pin	2055 mm
Length of track on ground	1031 mm
Reach @ Maximum Height	472 mm

⊖ Features

Lift-Arm Support	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Spark Arrestor Muffler	<input type="checkbox"/>
Bob-Tach Attachment System	<input checked="" type="checkbox"/>
Reverse Travel Stop Panel	N/A
Wide Track	<input checked="" type="checkbox"/>
Neutral Start Interlocks	<input type="checkbox"/>
Lift Arm Lockout With Manual Bypass	<input type="checkbox"/>
Tilt Lockout	<input type="checkbox"/>
Built-In Tie Down & Crane/Lift Locations	<input type="checkbox"/>
Ride-on Platform	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.