

# Skid-Steer Loaders / S650 Skid-Steer Loader

## Specifications & Options

■ Standard
  Optional
N/A Not Applicable

**Bobcat S650**

### ⊖ Engine

<b>Emissions Tier (EPA)</b>	Interim Tier 4
<b>Engine Cooling</b>	Liquid
<b>Engine Fuel</b>	Diesel
<b>Horsepower</b>	55.4 kW
<b>Turbocharged Engine</b>	<input checked="" type="checkbox"/>

### ⊖ Performance

<b>Rated Operating Capacity (SAE)</b>	1220 kg
<b>Tipping Load</b>	2440 kg
<b>Operating Weight</b>	3777 kg
<b>Travel Speed</b>	11,4 km/h
<b>Travel Speed (2-speed option)</b>	19,8 km/h

### ⊖ Capacities

<b>Fuel Tank</b>	103.1 l
------------------	---------

### ⊖ Hydraulic System

<b>System Relief @ Quick Couplers</b>	241,32 bar
<b>Auxiliary Std Flow</b>	87,1 l/min
<b>Auxiliary High Flow</b>	115,5 l/min

### ⊖ Dimansion

<b>Length</b>	3475 mm
<b>Length without Attachment</b>	2753 mm
<b>Length with Standard Bucket</b>	3475 mm
<b>Width</b>	1831 mm
<b>Width (with bucket)</b>	1880 mm
<b>Height</b>	2065 mm
<b>Height with Operator Cab</b>	2065 mm
<b>Height to Bucket Hinge Pin</b>	3150 mm
<b>Reach @ Maximum Height</b>	800 mm
<b>Turning Radius</b>	2106 mm
<b>Wheelbase</b>	1151 mm

### ⊖ Features

<b>Joystick Control</b>	<input checked="" type="checkbox"/>
<b>Air Conditioning</b>	<input checked="" type="checkbox"/>
<b>Adjustable Seat</b>	<span style="color: red;">■</span>
<b>Backup Alarm</b>	<span style="color: red;">■</span>
<b>BICS System (Interlock)</b>	<span style="color: red;">■</span>
<b>Cab Enclosure</b>	<input checked="" type="checkbox"/>
<b>Sound Option</b>	<input checked="" type="checkbox"/>
<b>Cab Heater</b>	<input checked="" type="checkbox"/>
<b>Operating Lights</b>	<span style="color: red;">■</span>
<b>Parking Brake</b>	<span style="color: red;">■</span>
<b>Radio</b>	<input checked="" type="checkbox"/>
<b>Rear Window</b>	<span style="color: red;">■</span>
<b>Top Window</b>	<span style="color: red;">■</span>
<b>Lift-Arm Support</b>	<span style="color: red;">■</span>
<b>Seat Belt</b>	<span style="color: red;">■</span>
<b>Suspension Seat</b>	<input checked="" type="checkbox"/>
<b>Two Speed Travel</b>	<input checked="" type="checkbox"/>
<b>Deluxe Instrumentation</b>	<input checked="" type="checkbox"/>
<b>Engine Shutdown</b>	<span style="color: red;">■</span>
<b>Hydraulic Bucket Positioning</b>	<input checked="" type="checkbox"/>
<b>High Flow Option</b>	<input checked="" type="checkbox"/>
<b>Auxiliary Hydraulics</b>	<span style="color: red;">■</span>
<b>Spark Arrestor Muffler</b>	<span style="color: red;">■</span>
<b>Bob-Tach Attachment System</b>	<span style="color: red;">■</span>
<b>Power Bob-Tach</b>	<input checked="" type="checkbox"/>
<b>ACS (Switchable Controls)</b>	<input checked="" type="checkbox"/>
<b>Ride Control</b>	<input checked="" type="checkbox"/>
<b>Rear Hydraulics</b>	<input checked="" type="checkbox"/>
<b>Horn</b>	<span style="color: red;">■</span>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.