

# Skid-Steer Loaders / S70 Skid-Steer Loader

## Specifications & Options

■ Standard
  Optional
N/A Not Applicable

**Bobcat S70**

### ⊖ Engine

<b>Emissions Tier (EPA)</b>	Tier 4
<b>Engine Cooling</b>	Liquid
<b>Engine Fuel</b>	Diesel
<b>Horsepower</b>	17,5 kW
<b>Turbocharged Engine</b>	N/A

### ⊖ Performance

<b>Rated Operating Capacity (SAE)</b>	318 kg
<b>Tipping Load</b>	686 kg
<b>Operating Weight</b>	1268 kg
<b>Travel Speed</b>	9,8 km/h

### ⊖ Capacities

<b>Fuel Tank</b>	24,6 l
------------------	--------

### ⊖ Hydraulic System

<b>System Relief @ Quick Couplers</b>	206,84 bar
<b>Auxiliary Std Flow</b>	37,1 l/min
<b>Auxiliary High Flow</b>	n/a

### ⊖ Dimansion

<b>Length</b>	1920 mm
<b>Length without Attachment</b>	1920 mm
<b>Length with Standard Bucket</b>	2471 mm
<b>Width</b>	902 mm
<b>Width (with bucket)</b>	914 mm
<b>Height</b>	1814 mm
<b>Height with Operator Cab</b>	1814 mm
<b>Height to Bucket Hinge Pin</b>	2400 mm
<b>Reach @ Maximum Height</b>	401 mm
<b>Turning Radius</b>	1491 mm
<b>Wheelbase</b>	721 mm

### ⊖ Features

<b>Joystick Control</b>	N/A
<b>Air Conditioning</b>	N/A
<b>Adjustable Seat</b>	■
<b>Backup Alarm</b>	■
<b>BICS System (Interlock)</b>	■
<b>Cab Enclosure</b>	<input checked="" type="checkbox"/>
<b>Sound Option</b>	<input checked="" type="checkbox"/>
<b>Cab Heater</b>	<input checked="" type="checkbox"/>
<b>Operating Lights</b>	■
<b>Parking Brake</b>	■
<b>Radio</b>	N/A
<b>Rear Window</b>	■
<b>Top Window</b>	<input checked="" type="checkbox"/>
<b>Lift-Arm Support</b>	■
<b>Seat Belt</b>	■
<b>Suspension Seat</b>	<input checked="" type="checkbox"/>
<b>Two Speed Travel</b>	N/A
<b>Deluxe Instrumentation</b>	N/A
<b>Engine Shutdown</b>	N/A
<b>Hydraulic Bucket Positioning</b>	<input checked="" type="checkbox"/>
<b>High Flow Option</b>	N/A
<b>Auxiliary Hydraulics</b>	■
<b>Spark Arrestor Muffler</b>	■
<b>Bob-Tach Attachment System</b>	■
<b>Power Bob-Tach</b>	N/A
<b>ACS (Switchable Controls)</b>	N/A
<b>Ride Control</b>	N/A
<b>Rear Hydraulics</b>	N/A
<b>Horn</b>	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.