

# Skid-Steer Loaders / S770 Skid-Steer Loader

## Specifications & Options

■ Standard
  Optional
N/A Not Applicable

**Bobcat S770**

### ⊖ Engine

<b>Emissions Tier (EPA)</b>	Tier 3
<b>Engine Cooling</b>	Liquid
<b>Engine Fuel</b>	Diesel
<b>Horsepower</b>	68,6 kW
<b>Turbocharged Engine</b>	<input checked="" type="checkbox"/>

### ⊖ Performance

<b>Rated Operating Capacity (SAE)</b>	1520 kg
<b>Tipping Load</b>	3039 kg
<b>Operating Weight</b>	4162 kg
<b>Travel Speed</b>	11,4 km/h
<b>Travel Speed (2-speed option)</b>	19,8 km/h

### ⊖ Capacities

<b>Fuel Tank</b>	103.1 L
------------------	---------

### ⊖ Hydraulic System

<b>System Relief @ Quick Couplers</b>	241,32 bar
<b>Auxiliary Std Flow</b>	87,1 l/min
<b>Auxiliary High Flow</b>	138.2 l/min

### ⊖ Dimansion

<b>Length</b>	3597 mm
<b>Length without Attachment</b>	2903 mm
<b>Length with Standard Bucket</b>	3597 mm
<b>Width</b>	1831 mm
<b>Width (with bucket)</b>	1880 mm
<b>Height</b>	2065 mm
<b>Height with Operator Cab</b>	2065 mm
<b>Height to Bucket Hinge Pin</b>	3353 mm
<b>Reach @ Maximum Height</b>	800 mm
<b>Turning Radius</b>	2179 mm
<b>Wheelbase</b>	1227 mm

### ⊖ Features

<b>Joystick Control</b>	<input checked="" type="checkbox"/>
<b>Air Conditioning</b>	<input checked="" type="checkbox"/>
<b>Adjustable Seat</b>	<span style="color: red;">■</span>
<b>Backup Alarm</b>	<span style="color: red;">■</span>
<b>BICS System (Interlock)</b>	<span style="color: red;">■</span>
<b>Cab Enclosure</b>	<input checked="" type="checkbox"/>
<b>Sound Option</b>	<input checked="" type="checkbox"/>
<b>Cab Heater</b>	<input checked="" type="checkbox"/>
<b>Operating Lights</b>	<span style="color: red;">■</span>
<b>Parking Brake</b>	<span style="color: red;">■</span>
<b>Radio</b>	<input checked="" type="checkbox"/>
<b>Rear Window</b>	<span style="color: red;">■</span>
<b>Top Window</b>	<span style="color: red;">■</span>
<b>Lift-Arm Support</b>	<span style="color: red;">■</span>
<b>Seat Belt</b>	<span style="color: red;">■</span>
<b>Suspension Seat</b>	<input checked="" type="checkbox"/>
<b>Two Speed Travel</b>	<input checked="" type="checkbox"/>
<b>Deluxe Instrumentation</b>	<input checked="" type="checkbox"/>
<b>Engine Shutdown</b>	<span style="color: red;">■</span>
<b>Hydraulic Bucket Positioning</b>	<input checked="" type="checkbox"/>
<b>High Flow Option</b>	<input checked="" type="checkbox"/>
<b>Auxiliary Hydraulics</b>	<span style="color: red;">■</span>
<b>Spark Arrestor Muffler</b>	<span style="color: red;">■</span>
<b>Bob-Tach Attachment System</b>	<span style="color: red;">■</span>
<b>Power Bob-Tach</b>	<input checked="" type="checkbox"/>
<b>ACS (Switchable Controls)</b>	<input checked="" type="checkbox"/>
<b>Ride Control</b>	<input checked="" type="checkbox"/>
<b>Rear Hydraulics</b>	<input checked="" type="checkbox"/>
<b>Horn</b>	<span style="color: red;">■</span>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.