

Skid-Steer Loaders / S850 Skid-Steer Loader

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat S850

⊖ Engine

Emissions Tier (EPA)	Tier 3
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	68,6 kW
Turbocharged Engine	<input checked="" type="checkbox"/>

⊖ Performance

Rated Operating Capacity (SAE)	1792 kg
Tipping Load	3583 kg
Operating Weight	4540 kg
Travel Speed	11,4 km/h
Travel Speed (2-speed option)	19,8 km/h

⊖ Capacities

Fuel Tank	124.2 L
-----------	---------

⊖ Hydraulic System

System Relief @ Quick Couplers	241,32 bar
Auxiliary Std Flow	87,1 l/min
Auxiliary High Flow	138.2 l/min

⊖ Dimansion

Length	3752 mm
Length without Attachment	3030 mm
Length with Standard Bucket	3752 mm
Width	2007 mm
Width (with bucket)	2032 mm
Height	2118 mm
Height with Operator Cab	2118 mm
Height to Bucket Hinge Pin	3658 mm
Reach @ Maximum Height	754 mm
Turning Radius	2261 mm
Wheelbase	1344 mm

⊖ Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Adjustable Seat	■
Backup Alarm	■
BICS System (Interlock)	■
Cab Enclosure	<input checked="" type="checkbox"/>
Sound Option	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	■
Parking Brake	■
Radio	<input checked="" type="checkbox"/>
Rear Window	■
Top Window	■
Lift-Arm Support	■
Seat Belt	■
Suspension Seat	■
Two Speed Travel	■
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	■
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	■
Spark Arrestor Muffler	■
Bob-Tach Attachment System	■
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	N/A
Ride Control	<input checked="" type="checkbox"/>
Rear Hydraulics	<input checked="" type="checkbox"/>
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.