

Specifications & Options

■ Standard
 Optional
 N/A Not Applicable

Bobcat 5600

⊖ Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	45,5 kW
Turbocharged Engine	<input checked="" type="checkbox"/>

⊖ Performance

Rated Operating Capacity (SAE)	680 kg
Operating Weight	2579 kg
Travel Speed	27,36 km/h
Travel Speed - Max	27,4 km/h
Travel Speed - Low	12,9 km/h
Travel Speed - Reverse	12,9 km/h
Machine Rated Capacity	998 kg
3-Point Hitch	n/a

⊖ Capacities

Fuel Tank	75,7 l
Cargo Box Bed Load Capacity	907 kg
Cargo Box Length	1422 mm
Cargo Box Width	1295 mm
Cargo Box Height	254 mm
Cargo Box Bed Load Height	970 mm
Total Vehicle Rated Capacity	1905 kg

⊖ Hydraulic System

Auxiliary Std Flow	71,5 l/min
Auxiliary Pressure	206.84 bar
Auxiliary High Flow	105,6 l/min

⊖ Dimansion

Length	4613 mm
Length without Attachment	3691 mm
Width	1524 mm
Width (with bucket)	1575 mm
Height	2057 mm
Height with Operator Cab	2057 mm
Bed Height From Ground	970 mm
Cargo Box Maximum Load	907 kg
Cargo Box Volume	0,5 m ³
Ground Clearance	235 mm
Turning Radius (AWS Mode)	2667 mm
Outside Turning Diameter	5334 mm

⊖ Features

Heater Air Conditioning	<input checked="" type="checkbox"/>
Work Lights	■
Enclosed Operator Cab (ROPS/FOPS)	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	■
Bob-Tach Attachment System	■
Joystick Control	■
Hydrostatic Transmission	■
Air Conditioning	<input checked="" type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.